

## technical data sheet

PennWhite Ltd, Aston Way, Midpoint 18 Business Park, Middlewich, Cheshire, CW10 0HS

### Description

Waxil 30 is an aqueous non-ionic/cationic emulsion of silicone oil and polyethylene wax.

### Applications

Waxil 30 is formulated for use in the printing industry as a surface finish additive on heat-set web-offset presses. It is also effective as a lubricant, softener or raising aid in the textile industry. Waxil 30 is an effective base for polishes and performs as a general release aid, lubricant and anti-rub agent.

### Product Features

Its wax content helps Waxil 30 provide a superior gloss finish to printed papers over silicone-only emulsions when used as a finishing agent.

### Method of Use

Waxil 30 is a multi-purpose emulsion and the methods of use will vary dependent upon the application. Dosage should be determined by trial.

### Toxicity & Handling

Waxil 30 is not classed as hazardous under current CLP regulations. Full details are available in the applicable Safety Data Sheet.

### Storage, Shelf Life & Packaging

Waxil 30 has a shelf life of 12 months when stored in original and unopened containers between 5°C and 30°C. It is available in 25kg, 200kg and 1,000kg packs.

### Typical Properties

- Appearance: Cream white opaque liquid
- Solids: 28.0 – 32.0 %
- pH: 5.0 – 7.0

*Please note; these are typical properties only and should NOT be construed or used as a specification for this product.*

(OPM3/D3)

TDS: 041

Issue: 06

Revised: 05/09/2018

Page 1 of 1



This product is manufactured in a facility whose Quality Management System is certified as being in conformity with ISO 9001:2015.



This product is manufactured in a facility which operates in line with the Chemical Business Association's Responsible Care program.

#### Technical Support Contact Details

Telephone: +44 (0)1606 734820

Fax: +44 (0)1606 837867

Email: [info@pennwhite.co.uk](mailto:info@pennwhite.co.uk)

Website: [www.pennwhite.co.uk](http://www.pennwhite.co.uk)